

Twin Master Combine

Standard Features:

*Heavy duty drive train equipped with:

*Cam type cut-out clutch

*Over running clutch

*1000 PTO input, 2 speed transmission:

*540 & 390 output

-or-

*500 & 350 output

*Approximately 18,500 lbs storage bin capacity

*13 foot dump height

*Twin bucket elevator system

*Twin vacuum system

*Twin straw discharge ports equipped with:

*Rear straw spreader

*Mechanical straw chopper

*Twin central flow threshing cylinders with left and right rotation

*Cylinders equipped with adjustable hardened threshing pins

*14' 10" working height

*13' 4" storage height

*Star feeder

*Transition auger

*Full length shaker table with final sieve

*Two final sieves 9/16" round and 1/2" X 1" slotted holes, standard

*Vacuum exhaust central discharge

*On the go universal offset swing tongue with 180° swivel gear box

*Floating 15 foot 8 bar soft finger pickup head

*In cab Ag Cam displays final shaker sieve and dump bin

*Optional Ag Cam can monitor 4 functions

*Touch Screen Monitor system with alarms & shaft speeds for threshing cylinder, shaker table, transition auger, bucket elevator, vacuum fan, straw choppers and bin full alarm. Monitor also controls pickup head on/off and speed

*Easy access clean-out ports

*Dump bin equipped with leveling augers

*30.5L x 32 16 ply tires

*Twin 28" diameter concaves with standard 20 mm holes

*Tilting tongue for added transport clearance

*Detachable header system

*Tractor requirements: 200 PTO horse power with 4 hydraulic remotes & 18 gpm



For more information see your local authorized Pickett Equipment dealer



www.pickettequipment.com 1-800-473-3559





